

RectorSeek™ BETTER BUBBLE™

Leak Locator

DESCRIPTION:

RectorSeek™ BETTER BUBBLE is our newest and most advanced leak locator formula. It detects leaks of refrigerant gases, air, oxygen, and most other gases. Its thick formula can be used at various temperature and pressure applications to pinpoint the smallest leak quickly and easily.

APPLICATIONS:

RectorSeek™ BETTER BUBBLE is formulated for use on all types of pipe, tubing, valves, tanks, pressure vessels, condenser/evaporator coils, refrigeration coils, and many other similar applications. It is biodegradable and environmentally friendly.

The product does not contain any oils, halogens, ammonia, or amines. It will not corrode metal surfaces or attack plastic or rubber. Is not chemically reactive with refrigerant oils.

INSTRUCTIONS:

1. If frozen, thaw before using.
2. Apply full strength by spray or dauber directly on pressurized joint or seam to be tested.
3. Large stable bubbles will appear at location of leaking gas. Very low pressure leaks may produce smaller, slower forming bubbles.
4. After testing, wipe off and allow to air dry.

PRECAUTIONS:

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

PRECAUTIONS: Do not take internally. May be harmful if swallowed in large quantities. May cause mild eye or skin irritation. Avoid contact with eyes and skin. Wash after handling. **FIRST AID:** For any overexposure, get immediate medical attention after first aid is given. **Eyes** - Flush 15 minutes with clean water. **Skin** - Wash with soap and water. **Ingestion** - Only if conscious, give large amounts of water and INDUCE VOMITING. **FIRE AND SPILLS:** For fire, use water fog, CO₂, foam or dry chemicals. Wipe up spills to prevent footing hazard. **STORAGE AND HANDLING:** Keep container closed when not in use. Do not reuse empty container. **KEEP OUT OF REACH OF CHILDREN.**

For additional information, refer to Material Safety Data Sheet.

SPECIFICATIONS:

Wt/Gal @ 77° F	8.7 ± .5 lbs./gal.
Flash Point SETA CC	368° F
Color	Clear Bright Blue
Shelf Life	2 years



FGG/BM/CZ™ System Compatible indicates that this product has been tested and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster®, and Corzan® pipe and fittings. FlowGuard Gold®, BlazeMaster® and Corzan® are licensed trademarks of the Lubrizol Corporation.

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

LIMITED WARRANTY:

RectorSeal makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal shall not be liable for incidental or consequential damages.

MANUFACTURED BY
RectorSeal • 2601 Spenwick Drive • Houston, Texas 77055-1035, USA
Telephone: 713-263-8001 or 1-800-231-3345 Fax: 713-263-7577 or 1-800-441-0051
www.rectorseal.com