



HUMIDEX TABLETS™

HUMIDIFIER TREATMENT

DESCRIPTION

HUMIDEX TABLETS™ precipitate scale and silt as a soft, easily rinsable slurry that is flushed out of the humidifier with almost no effort. Float valves, pumps, evaporator pads, plates and electrodes are kept free of hard water encrustations which either make the humidifier inoperative or inefficient.

CHARACTERISTICS

- Prevent and eliminate hard water scale, encrusted silt and corrosion
- For use in central and portable humidifiers
- Keeps humidifiers and vaporizers clean and efficient.
- Easy to use tablets.

APPLICATIONS

HUMIDEX TABLETS™ are used to remove hard water mineral scale, encrusted silt and corrosion from central and portable humidifiers. **HUMIDEX TABLETS™** can be used in wick, power and portable humidifiers.

PACKAGING

<u>Code</u>	<u>Size</u>	<u>Qty./Case</u>	<u>Lbs./Case</u>	<u>Cu. Ft./Case</u>
88442	12 tablet tube	24	4	0.16

HUMIDEX TABLETS™ HUMIDIFIER TREATMENT

INSTRUCTIONS

READ ALL DIRECTIONS, MSDS AND WARNINGS ON LABEL BEFORE USING

- Drop HUMIDEX TABLETS™ into water reservoir.
- Use dosage recommended in table.
- Rinse out precipitated lime solids and silt before each application of tablets.

In **Portable Humidifiers** with water reservoirs of at least 7 gallons capacity, an entire season's treatment may be applied at once.

Full control is normally achieved by these doses. In exceptional cases double the dosage.

In **Vaporizers**, put one tablet in water with each use.

For each 10 gallons of water evaporated per day:

<u>Water Hardness</u>	<u># Tablets</u>	<u>Frequency</u>
Soft – Medium (up to 10 grains)	2	Every 3 months
Medium – Hard (up to 20 grains)	2	Every 1 ½ months
Hard (up to 30 grains)	2	Every month

Keep container sealed to avoid swelling of tablets

For additional technical information, call Toll Free 1-800-231-3345

PRECAUTIONS

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

**KEEP OUT OF REACH OF CHILDREN.
AVOID CONTAMINATION OF FOOD.**

FIRST AID: Skin: Wash off with soap and water. **Ingestion:** Induce vomiting. Call physician immediately.

For additional information, refer to Material Safety Data Sheet.

SPECIFICATIONS

Wt/Gal @ 77°F	NA
Flash Point SETA CC	NA
Color	Blue
Shelf Life	2 years minimum

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

LIMITED WARRANTY

Rectorseal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. **THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®.** The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and Rectorseal® shall not be liable for incidental or consequential damages.

MANUFACTURED BY

Rectorseal® • 2601 Spenwick Drive • Houston, Texas 77055-1035
Telephone: 713-263-8001 or 1-800-231-3345 Fax: 713-263-7577 or 1-800-441-0051
www.rectorseal.com