

ICC-ES Report

PMG-1070

ICC-ES | (800) 423-6587 | (562) 699-0543 | www.icc-es.org

Reissued 02/2018
This report is subject to renewal 02/2019

EVALUATION SUBJECT:

SURESEAL[®] – BARRIER TYPE FLOOR DRAIN TRAP SEAL PROTECTION DEVICES ("DEVICE")

DIVISION:

22 00 00—PLUMBING

SECTION:

22 13 16—SANITARY WASTE AND VENT PIPING

Report Holder:

RECTORSEAL, LLC

2601 SPENWICK DRIVE
HOUSTON, TX 77055

Look for the ICC-ES marks of Conformity!



ICC-ES PMG Product Certificate

PMG-1070

Effective Date: February 2018

This listing is subject to re-examination in one year.



www.icc-es-pmg.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

CSI: DIVISION: 22 00 00—PLUMBING
Section: 22 13 16—Sanitary Waste and Vent Piping

Product certification system:

The ICC-ES product certification system includes testing samples taken from the market or supplier's stock, or a combination of both, to verify compliance with applicable codes and standards. The system also involves factory inspections, and assessment and surveillance of the supplier's quality system.

Product: SureSeal® - Barrier Type Floor Drain Trap Seal Protection Devices ("Device")

Listee: RectorSeal, LLC
2601 Spenwick Drive
Houston, Texas 77055
www.rectorseal.com

Compliance with the following codes:

2018, 2015, 2012, 2009 and 2006 *International Plumbing Code*® (IPC)
2018, 2015, 2012, 2009 and 2006 *International Residential Code*® (IRC)
2015, 2012, 2009 and 2006 *National Standard Plumbing Code*® (NSPC)
2015, 2012, 2009 and 2006 *Uniform Plumbing Code*® (UPC)*

**Uniform Plumbing Code*® is a copyrighted publication of the International Association of Plumbing and Mechanical Officials

Compliance with the following standards:

ASSE 1072-2007, Performance Requirements for Barrier Type Floor Drain Trap Seal Protection Devices, American Society of Sanitary Engineering.
ICC-ES LC1015, PMG Listing Criteria for Elastomeric, Normally Closed, Floor Drain Evaporation Resistant Sealing System (Oct 2010)

Identification:

The product and/or package must bear the SureSeal® name, the model number and the ICC-ES PMG listing mark.

Installation:

SureSeal® trap primer alternates are to be installed in accordance with the manufacturer's instructions and the applicable code.

Models:

MODEL	Device SIZE		FLOW RATE	
	Inches	mm DN	GPM	L/M
SS2009V	2	40	12.0	45.4
SS3009V	3	50	34.0	128.7
SS3509V	3 ¹ / ₂	80	52.0	196.6
SS4009V	4	100	73.0	276.4
SS2009Plus	2	40	12.0	45.4
SS3009Plus	3	50	34.0	128.7
SS4009Plus	4	100	73.0	276.4

Conditions of listing:

1. SureSeal[®] devices, recognized by this listing, are intended to serve as alternates to the code-required trap primer. They must serve a functioning trap.
2. The plumbing systems must be installed in accordance with the applicable codes.
3. The "Device" must be accessible.
4. SureSeal[®] trap primer alternates are manufactured under a quality control program with annual surveillance inspections.

