



**RECTORSEAL**

# Condensate Overflow Control Products




**Switch to  
the Best**

**SAFE-T-SWITCH<sup>®</sup>**

**The Most Reliable  
Switch on the Market**

*Low Voltage Condensate Overflow  
Shut-off Switches*



**Easy to Install  
& Service**

**Magnetic Reed  
Switch Design**

**Connect To Either  
Red or Yellow Wire**

**Simple to Use**

**No Need to  
Level Switch**

**Install Vertically  
or Horizontally**

**Code Compliant**

**UL Listed 508**

SAFE-T-SWITCH<sup>®</sup> detects clogged air conditioner condensate drains and shuts off the system to prevent water damage to floors, walls and ceilings. While A/C flooding can result from other problems, clogged A/C drains are the most common cause of water damage and mold growth from air conditioners. Model SS3 is designed to fit in either primary or auxiliary drain pans. If plenum rating is required use SS2AP.



# Model SS1



*For Installation on Primary Drains or Auxiliary Drain Outlets*

Safe-T-Switch® model SS1 can be installed horizontally or vertically, inline or on the primary pan's auxiliary drain outlet by using the included 3/4" adapter, bushing and cap. It can be installed on a sloping line and does not need to be level or plumb. The switch and cap on the SS1 are easily removed for cleaning and for servicing condensate drain lines.

**MODEL SS1 - Product #97630**



# Model SS2



*For Installation on Primary Pan Auxiliary Outlet*

Using the 3/4" adapter, the SS2 can be installed on the auxiliary outlet of the primary drain pan. The patented magnetic reed switch allows it to be installed off-center and still function correctly. The SS2 also provides easy access to the switch and the primary drain line for service.

**MODEL SS2 - Product #97635**



# Model SS3



*For Installation on Primary & Auxiliary Drain Pans*

The specially designed steel mounting bracket clips firmly over the edge of most drain pans and the slim-profile SS3 can be installed on primary or auxiliary drain pans. The patented Magnetic Reed Switch allows it to be installed off-center and still perform correctly.

**MODEL SS3 - Product #97645**



# Model SS2AP



*For Installation on Primary Pan Auxiliary Outlet When Plenum Rating is Needed*

The SS2AP is plenum rated and listed to UL-2043. Using the 3/4" adapter, it can be installed on the auxiliary outlet of the primary drain pan.

**MODEL SS2AP - Product #97640**



[www.RectorSeal.com](http://www.RectorSeal.com)

2601 Spenwick Dr. - Houston, TX 77055

PH: 713-263-8001 - 800-231-3345

FAX: 713-263-7577 - 800-441-0051

For more product information,

Scan this QR Code

