

**RECTORSEAL® PTFE TAPE**

Pipe thread sealant tape

**Description**

RectorSeal® PTFE Tape can be used on all metal and plastic threaded pipe joints to seal against internal pressure at temperatures from -450°F to +550°F (-267°C to 287°C). It is available in a wide variety of sizes.

**Characteristics | Features**

- Resistant to most liquids or gases
- Completely inert.
- Non-toxic
- Non-flammable

**Applications**

Rectorseal® PTFE Tape can be used on all metal and plastic threaded pipe joints.

**Packaging**

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet per Case
35942	½" x 260"	12	1	0.67
35943	½" x 520"	12	1	0.72
35944	½" x 1296"	12	1	1.20
35945	¾" x 260"	12	1	1.13
35946	¾" x 520"	12	1	1.13
35947	¾" x 1296"	12	2	1.17
35949	1" x 520"	12	2	0.67

## Instructions

*Read all directions, SDS and warnings on label before using*

1. Clean pipe threads of all debris and oils.
2. Wrap tape tightly onto the threads in the direction the fitting will be threaded when making the joint.
3. Use enough layers of wrapping to ensure a good seal will be made. This will depend on how good the threads on the pipe and fitting have been made.
4. Tighten in the normal manner.
5. Do not reuse a taped joint without removing the old tape and replacing it with new.

*For additional technical information, call toll free 1-800-231-3345.*

## Precautions

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,  
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300  
CAUTION - COMBUSTIBLE

This product is chemically inert and non-toxic. Precaution should be taken, however to ensure persons do not take this material orally. If not applied to pipe threads correctly, shreds of this product may come loose in the pipe and stop up valves, faucets, and spray nozzles.

KEEP OUT OF REACH OF CHILDREN.

*For additional information, refer to Safety Data Sheet.*

## Specifications

Shelf life    Unlimited

*Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.*

## Limited Warranty

RectorSeal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed, we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal® shall not be liable for incidental or consequential damages.

Manufactured by

**RectorSeal®**

2601 Spenwick Drive • Houston, TX 77055 USA  
713-263-8001 • Fax 713-263-7577

Toll-free 800-231-3345 • Fax 800-441-0051

J-16