

# NoKink™ Frequently Asked Questions



NoKink™ Flexible Refrigerant Connectors



A CSW Industrials Company

# NoKink™ Frequently Asked Questions





A CSW Industrials Company

## NoKink™ Frequently Asked Questions

**Q: What sizes and lengths are available?**

**A: 1/4", 3/8", 1/2" and 5/8" ID all sizes 36" and 72" long with 3" copper stubs on both ends. And now 3/4" and 7/8" x 36"**

**Q: Can they be flared?**

**A: Yes they can be flared or soldered/brazed.**



A CSW Industrials Company

# NoKink™ Frequently Asked Questions



## NoKink™ Frequently Asked Questions

**Q: What are they made of? Do they have rubber inside?**

**A: No they do not have rubber in them. The flexible section is corrugated 304L SS surrounded by SS braiding.**





A CSW Industrials Company

## NoKink™ Frequently Asked Questions

**Q: Is NoKink™ UL listed?**

**A: NoKink™ is listed to UL 207.**

**Q: What standards does NoKink™ meet?**

**A: Listed to UL 207. Copper tubing confirms to ASTM B280. Stainless Tube conforms to ISO 10380. Burst strength conforms to SAE J 2064, modified pressure for R410A. Cleanliness test conforms to SAE J 2064.**

**Q: Do I have to insulate the NoKink™**

**A: Yes**



A CSW Industrials Company

## NoKink™ Frequently Asked Questions

**Q: What is maximum working pressure?**

**A: 800 PSI**

**Q: What is burst pressure?**

**A: Burst strength is higher than 4000 PSI**



A CSW Industrials Company

## NoKink™ Frequently Asked Questions

A look inside a NoKink™





# NoKink™ Frequently Asked Questions

- 80% silver solder

