



# NFP75 3" Telescoping Wall Sleeve

## Description

The NFP75 3" Telescoping Wall Sleeve is used to create a clean sealed wall penetration for the interconnecting piping and cables typically used in Ductless Mini-Split installations. Proper use of the NFP75 Wall Sleeve along with effective maintenance will allow for a more energy efficient installation and long term cleanliness of the evaporator and blower wheel on high wall ductless installations. Telescopes from 4" to 7.5". If wall is thicker then 7.5" two NFP75s and be joined to create custom lengths as needed.

## Characteristics | Features

- 3" x 4"-7.5"
- 3 sections
- Polyethylene
- Telescoping

## Applications

Any wall penetration needing a clean, sealed sleeve for routing piping and or cabling through.



## Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet per Case
83017	1 sleeve assembly	10	1 lb	.55

## Instructions

Determine correct location for wall penetration. Drill 3" diameter hole through wall. Measure wall thickness and adjust wall sleeve to same length up to 7.5". If wall is thicker then 7.5" add sections from a second NFP75 until desired length is achieved on the interior flange place a bleed of caulk or other sealant product and slide NFP75 from the interior wall outward until flange is flush to interior wall surface. Route piping and cabling through NFP75 as needed and complete installation of indoor unit. Using appropriate material seal any gaps in and around the exterior edge of the NFP75 and piping/cabling. If desired some loose insulating material can be added inside the sleeve for better thermal performance of wall structure.

For additional technical information, call Toll Free 1-800-231-3345

## Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANT ABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

**RectorSeal®**

2601 Spenwick Drive • Houston, TX 77055 USA  
713-263-8001 • Fax 713-263-7577

Toll-free 800-231-3345 • Fax 800-441-0051